

---

## Device Summary Report

---

### 1. Conformance

<b>GSRN No.</b>	: 950110126000001701
<b>Product Name</b>	: Senstech MM3U IC
<b>Trade Mark</b>	: N/A
<b>Product ID</b>	: N/A
<b>Manufacturer</b>	: Senstech Sdn. Bhd.
<b>Client</b>	: Senstech Sdn. Bhd.
<b>Standard(s)</b>	: EPCglobal Class-1 Generation-2 UHF Protocol V1.1.0 for Communications at 860MHz to 960 MHz and EPCglobal Radio Frequency Identity Protocols Class-1 Generation-2 UHF RFID Conformance Requirements, Version 1.0.5 and Interoperability Test System for EPC Compliant Class-1 Generation-2 UHF RFID Devices, Version 1.2.5

Tag Conformance Badge	
Frequency Range	860 - 960 MHz
Backscatter Modulation Type	ASK, PSK
Temperature range	-40C to +85C
Optional Command Support	Access, BlockWrite, BlockErase

## 2. Interoperability

### IC

Name/GSRN of Certified IC	MM3U IC 950110126000001701
Tag Used(model #)	Small Folded Dipole
Frequency Bands Tested	862-870 MHz <input checked="" type="checkbox"/> 902 – 928 MHz <input checked="" type="checkbox"/>
*Tested Range:	1 meter
Notes	Tag configurations that utilize the identical certified IC may be as interoperable as the tested tag. See tag manufacturer for selection of tags for this IC.

IC – Integrated Circuit

\* The distance between the reader antenna and tag used for testing

Backscatter Encoding	M	Backscatter Data Rate (kbps)	Tari (µs)			
			6.25 – 12.5	12.5 – 18.75	18.75 – 25	
FM0	1	640 – 320	Mod: PR PIE:2:1 DR:64/3 Funct: P Sirit INfinity 510 RFID Reader			
		320 -256				
		256 – 160				
		160 – 40				
Subcarrier	2	320 – 128				
		128 – 20				
	4	160 – 64				
		64 – 10	Mod: DS PIE:1.5:1 DR:8 Funct: P Sirit INfinity 510 RFID Reader		Mod:PR PIE:2:1 DR:64/3 Funct: P Impinj Speedway RFID Reader	
		8	80 – 32	Mod: PR PIE:2:1 DR:64/3 Funct: P Sirit INfinity 510 RFID Reader		
			32 – 5			

**Appendix: Keys**

DS	DSB-ASK
SS	SSB-ASK
PR	PR-ASK
X:1	PIE ratio

**Optional Gen 2 functionality indicated under Funct:**

- P Access passwords supported
- U User memory supported
- WT Write-able TID supported